

Pars Line Track Mounted

Pars Line Track Mounted / I02.LL.19902



* Code example / Kod örneği:

I02.LL.19902.0626.032.030.830.01

- 1- Product code / Armatür kodu
- 2- Length / Uzunluk
- 3- Power / Güç
- 4- Beam Angle / Işık Açısı
- 5- CRI / Kelvin
- 6- Colour / Ürün renk
- 7- Control type / Kontrol tipi

Track Adaptor

Ray Soketi



Length / Uzunluk (A)	CRI	Order Code / Sipariş Kodu	Kelvin	17W 250mA Im	23W 350mA Im	32W 500mA Im
626mm	CRI>80	I02.LL.19902.(...).(...). (...)	2700K	1729	2390	3257
			3000K	1784	2466	3362
			3500K	1819	2515	3428
			4000K	1856	2566	3497
			5000K	1912	2644	3603
	CRI>90	I02.LL.19902.(...).(...). (...)	2700K	1607	2222	3029
			3000K	1658	2292	3124
			3500K	1691	2338	3187
			4000K	1726	2387	3253
			20W 250mA Im	28W 350mA Im	39.5W 500mA Im	
781mm	CRI>80	I02.LL.19902.(...).(...). (...)	2700K	2161	2988	4072
			3000K	2230	3084	4203
			3500K	2274	3145	4286
			4000K	2320	3208	4372
			5000K	2390	3305	4504
	CRI>90	I02.LL.19902.(...).(...). (...)	2700K	2009	2778	3787
			3000K	2073	2866	3906
			3500K	2114	2923	3984
			4000K	2158	2984	4067
			24W 250mA Im	33.5W 350mA Im	47W 500mA Im	
936mm	CRI>80	I02.LL.19902.(...).(...). (...)	2700K	2593	3585	4887
			3000K	2676	3700	5043
			3500K	2729	3773	5143
			4000K	2784	3849	5246
			5000K	2868	3966	5405
	CRI>90	I02.LL.19902.(...).(...). (...)	2700K	2411	3334	4544
			3000K	2487	3439	4687
			3500K	2537	3507	4781
			4000K	2590	3581	4880
			28W 250mA Im	39W 350mA Im	54W 500mA Im	
1091mm	CRI>80	I02.LL.19902.(...).(...). (...)	2700K	3111	4300	5865
			3000K	3211	4440	6050
			3500K	3275	4530	6170
			4000K	3340	4620	6295
			5000K	3440	4760	6485
	CRI>90	I02.LL.19902.(...).(...). (...)	2700K	2895	4000	5450
			3000K	2985	4125	5625
			3500K	3045	4200	5735
			4000K	3108	4300	5855

2	Length / Uzunluk (A)	3	Watt - Driving Current / Watt - Sürüş Akımı	4	Beam Angle / Işık Açısı	5		6	Product Color / Ürün Renk		
						CRI / Kelvin					
626mm		17W 23W 32W	17W (Direct) - 250mA 23W (Direct) - 350mA 32W (Direct) - 500mA	ME	30° - Medium	827	CRI>80 - 2700K	927	CRI>90 - 2700K	01	white
						830	CRI>80 - 3000K	930	CRI>90 - 3000K	02	ral 9010
781mm		20W 28W 39.5W	20W (Direct) - 250mA 28W (Direct) - 350mA 39.5W (Direct) - 500mA	WF	60° - Wide Flood	835	CRI>80 - 3500K	935	CRI>90 - 3500K	03	black
						840	CRI>80 - 4000K	940	CRI>90 - 4000K	04	gray
936mm		24W 33.5W 47W	24W (Direct) - 250mA 33.5W (Direct) - 350mA 47W (Direct) - 500mA			850	CRI>80 - 5000K			05	dark gray
										06	special color
1091mm		28W 39W 54W	28W (Direct) - 250mA 39W (Direct) - 350mA 54W (Direct) - 500mA								

(...) / Complete Code / Komple Kod