

Etange




* Code example / Kod örneği:

O07.LL.19340 . 1224 . 20 . 830 . 01


- 1- Product code / Armatür kodu
- 2- Length / Uzunluk
- 3- Power / Güç
- 4- CRI / Kelvin
- 5- Colour / Ürün renk
- 6- Control type / Kontrol tipi



Beam Angle / Işık Açısı



Technical Drawing / Teknik Çizim



Product Data / Armatür Data	
Item No / Ürün Kod	O07.LL.19340.1224.20.830.01
Family Name / Aile Adı	Etange
Material / Malzeme	Cast PC Body / Baskı Polikarbon Gövde
Form / Biçim	Linear / Lineer
Profile Width / Profil Geniřlięi	92mm
Profile Height / Profil Yükseklięi	90mm
Installation Type / Kurulum Türü	Suspendant, Surface Mounted and Track Mounted / Sarkıt, Sıvaüstü ve Raya Monteli
Efficiency / Verimlilik	>120lm/W
CRI	80
Light Distribution / Işık Daęılımı	Symmetric Wide Flood / Simetrik Geniř Açı
Protection Rating / Koruma Sınıfı	20
Lifetime / Armatür Ömrü	L70 / B50 50000 h
Optic / Optik	Opal Diffuser / Opal Pleksi

EN

- Polycarbonate PMMA body.
- Mains voltage: 220-240V / 50-60Hz.
- Clever thermal design.
- 1-10V, DALI and switch dimming options available upon request.
- Opal diffuser.
- Emergency kit system can be integrated.
- Easy mounting by practical metal clips.
- Led colour temperatures are optionally 2700K, 3000K, 3500K, 4000K, 5000K and 6500K.
- Weatherproof and durable silicone rubber gasket.
- High colour consistency: <3 SDCM
- Up to 120lm/W efficiency.

TR

- Polikarbonat PMMA gövde.
- 220-240V / 50-60Hz enerji giriřli.
- Akıllı soęutma tasarımı.
- 1-10V, DALI ve switch dim seçenekleri bulunmaktadır.
- Opal difüzör.
- Acil aydınlatma kit sistemi uygulanabilir.
- Metal klipsler sayesinde kolay montaj edilebilir.
- 2700K, 3000K, 3500K, 4000K, 5000K ve 6500K renk sıcaklıęı seçenekleri mevcuttur.
- Su geçirmezlięi saęlayan silikon conta.
- Yüksek LED renk uyumu: <3 SDCM
- 120lm/W'a kadar ulařan verim.

Etange

Etange / 007.LL.19340

Lenght / Uzunluk (A)	CRI	Order Code / Sipariş Kodu	Kelvin	20W 125mA lm	40W 250mA lm
1224mm	CRI>80	007.LL.19340 . (...) . (...) . (...) . (...)	2700K	2207	4072
			3000K	2277	4202
			3500K	2312	4267
			4000K	2401	4430
			5000K	2436	4495
			6500K	-	-
Lenght / Uzunluk (A)	CRI	Order Code / Sipariş Kodu	Kelvin	25W 125mA lm	50W 250mA lm
1524mm	CRI>80	007.LL.19340 . (...) . (...) . (...) . (...)	2700K	2741	5018
			3000K	2828	5179
			3500K	2872	5259
			4000K	2982	5460
			5000K	3026	5540
			6500K	-	-

2	Lenght / Uzunluk (A)	3	Watt - Driving Current / Watt - Sürüş Akımı	4		5	Product Color / Ürün Renk
				CRI	Kelvin		
(...)/ Complete Code / Komple Kod	1224mm	20W 40W	20W (Direct) - 125mA 40W (Direct) - 250mA	827	CRI>80 - 2700K	<input type="checkbox"/> 01 white <input type="checkbox"/> 02 ral 9010 <input checked="" type="checkbox"/> 03 black <input type="checkbox"/> 04 gray <input type="checkbox"/> 05 dark gray <input type="checkbox"/> 06 special color	
				1524mm	25W 50W		25W (Direct) - 125mA 50W (Direct) - 250mA
	835	CRI>80 - 3500K					
	840	CRI>80 - 4000K					
	850	CRI>80 - 5000K					
	865	CRI>80 - 6500K					

