



- Aluminium body.
- Microprismatic PMMA opal diffuser.
- Mains voltage: 220-240V / 50-60Hz.
- 1-10V, DALI and switch dimming options available upon request.
- Over 120lm/W efficiency.
- Emergency kit system can be integrated.
- Basic colours: white, black, silver, antracite dark gray and special color options available upon request.
- 24V DC Electronic Led driver positioned outside luminaire.
- Steel suspension cord with up to 5mt lenght option.
- With lower profile height slim appearance.

- Alüminyum gövde.
- Mikroprizmatik PMMA opal difüzörü.
- 220-240V / 50-60Hz enerji giriřli.
- 1-10V, DALI ve switch dim seçenekleri bulunmaktadır.
- 120lm/W'in üzerinde verimlilik.
- Acil aydınlatma kit sistemi uygulanabilir.
- Standart renkler: beyaz, siyah, gri, antrasit koyu gri ve isteğe baęlı özel renk seçenekleri mevcuttur.
- 24V DC Led trafosu armatürün dıřındadır.
- 5mt uzunluk seçeneğine kadar tercih edilebilir çelik sarkıt tel.
- Kısa profil yükseklięi ile zarif görünüm.

Sivo Slim / I02.LL.14130.100

Order Code / Ürün Kodu	I02.LL.14130.100	
LED	SMD LED	
Led Power / Led Gücü	57.5W	
System Power / Sistem Gücü	62.5W	
Lumen Output from Fixture / Armatür Çıkış Lümeni CRI>80	2700K	6850
	3000K	7060
	3500K	7200
	4000K	7345
	5000K	7565
Product Diameter / Ürün Çapı (A)	Ø1000mm	
Product Diameter / Ürün Çapı (B)	Ø850mm	
Mains Switch Dim Option / 220V Anahtar Dim Opsiyonu	✓	
1-10V Dimming Option / 1-10V Dim Seçeneęi	✓	
Dali Dimming Option / Dali Dim Seçeneęi	✓	



Suspension Cord
Ray Sarkıtma Teli

